



► Model I-IP15X

Informer15 IP enabled 15 W hazardous location speaker

The Informer15 Speaker is a 15-watt, IP-enabled indoor and outdoor speaker. The Informer15 can be used as a warning and alert device with both audible and visual indicators in hazardous locations. The audible capabilities include locally stored high-quality, high-powered tones and voice messages. The visual indicators include the use of external devices* such as: message board/scrolling display sign support, strobes, lights, and beacons. The Informer15 can be equipped with up to four local initiation devices (external switches*) to activate the unit locally and to the Commander® controller for mass notification communications.

The Informer15 Speaker has an internal 15-watt amplifier/driver to deliver tone warnings and intelligible voice messages from Informer15 stored memory. The Informer15 also has several unique capabilities when working with the Federal Signal Commander software. Using Commander software, the Informer15 can play text-to-speech, stream WAV files or can broadcast live PA. In addition, Commander software can perform a talk/listen to individual Informer15's to allow call box type communications. The Informer15 also has remote volume control for optimizing sound levels across your alerting area. The remote volume control also includes an ambient-noise-monitoring capability to automatically adjust the volume depending on external noise levels.

The Informer15 allows connection of up to four external switches to activate predefined alert events. The Informer15 can be programmed and configured as a standalone device to only use the inputs to activate the Informer15. This may be useful if the location has no network connectivity, but where voice and tone alerts from locally activated inputs is required. The Informer15 can be networked later and the activations can be brought into the Commander system for full system capability. When the Informer15 is networked using the Commander software, alerts initiated at the Informer15 can be used to activate other devices. The Commander software system can also alert emergency personnel via email, SMS, and hand-held radios using optional messaging software.

A P P L I C A T I O N S

- Indoor and Outdoor Locations
- Loud industrial facilities
- Muster or call stations
- Weather alerting
- Industrial hazardous locations
- Food processing locations
- For use with video security systems
- Plant wide alerting System
- Plant wide Live-PA announcements
- Modbus TCP enabled

HAZARDOUS LOCATION RATING:

T-CODE AT MAXIMUM AMBIENT TEMPERATURE 65°C

Hazardous Location	Constant on	5 min. Duty Cycle
Class I, Division 2, Groups A, B, C, D	T2B	T3A
Class II, Division 2, Groups F, G	T6	T6
Class III	T6	T6

Scan to download the
Informer15 Application Note



I-IP15X Hazardous Locations 15W IP-enabled Speaker



FEATURES

- Outdoor or indoor IP-enabled speaker for audible and visual alerts
- Speaker rated at 112 dB for tones and 107 dB for pink noise at 10 feet
- Seven standard built-in warning signals: Wail, Steady, Alternate Wail, Alternate Steady, Pulsed Wail, Pulsed Steady, Auxiliary Chime
- Broadcasts live voice, text-to-speech, and pre-recorded voice or tone files
- Deliver intelligible voice messages from locally pre-recorded files
- Pre-recorded files: up to 4000 messages with 17 hours of recording time
- Ambient-noise-level monitoring with automatic volume control
- Each device can be remotely configured for volume and noise-level adjustments
- Speaker as microphone for talk-back feature
- Alerts can be sent to single devices, groups or zones, or all devices
- Wall mount
- Four local alarm initiation inputs to activate unit locally or standalone operation Momentary mode: contact closure sounds alarm for programmed duration. Continuous mode: sounds alarm for duration of closure
- One open collector output paired with 24 Vdc for controlling an external relay
- High-intensity LED light that can be activated independently or with messages
- Models available with white, red, amber, blue, and green LEDs
- Wide variety of flash patterns
- Power over Ethernet using 802.3at PoE+ 25.5 W
- Wide operating temperature range
- Federal Signal Commander software provides activation, full two-way control, and status monitoring
- Allows remote software upgrades
- NEMA 4x enclosure
- UL and cUL listed for class1, Division 2; Class II, Division 2; Class III locations
- Complies with FCC Title 47, Part 15

SPECIFICATIONS

- Input Voltage: Power over Ethernet (PoE+ 802.3at) requires 25.5W
- Alarm initiating inputs: Four optically Isolated Inputs
- Audio Storage: Prerecorded files—up to 4000 messages with up to 17 hours of recording time
- Operating temperature range: -30°C to +65°C/-22°F to +149°F
- 13.9 inches x 10.2 inches x 10.0 inches
35.3 cm x 25.9 cm x 25.4 cm

* External devices must be rated for use in hazardous locations.

HOW TO ORDER

Description	Part Number
15W IP-enabled speaker with White LED	I-IP15X-W
15W IP-enabled speaker with Red LED	I-IP15X-R
15W IP-enabled speaker with Blue LED	I-IP15X-B
15W IP-enabled speaker with Amber LED	I-IP15X-A
15W IP-enabled speaker with Green LED	I-IP15X-G

Commander is a registered trademark of Federal Signal Corporation.