

# ESSENTIAL CONSOLE PROCESSOR DATA SHEET



The Mindshare Essential Console system provides principal functions and features necessary for commercial dispatch applications. The Essential Console is a Single Board Computer providing users with the tools they require to perform dispatching duties, utilizing an embedded customized Linux operating system, thus eliminating exposure to updates and distractions that aren't necessary for the dispatch environment.

### **SYSTEM**

The Essential Console application provides a predefined user-friendly interface with a purely web-based configuration platform, enabling a quick and easy deployment. The Essential Console allows the user to monitor up to eight channels simultaneously, with access to an unlimited number of additional channels/talk groups. The user can quickly change any module to monitor a different channel with just a few clicks of a mouse. This can be accomplished without the need for 'backroom configuration changes'.

### **PROCESSOR**

The Essential Console's integrated processor provides all the power necessary without the need for a separate desktop PC, audio processors or additional hardware. The sleek and compact design of the processor allows it to be mounted directly behind the monitor or under the desk, optimizing the dispatch work area.

### **LOCATION VIEW**

The Location view displays the location of radio units which have reported their GPS coordinates on a map. The map will update the location of the radio unit each time new GPS coordinates have been received. This feature requires an additional license fee and can only be used when the console system has been interfaced to a compatible radio system. This feature also requires an internet connection to allow map services.





# ESSENTIAL CONSOLE PROCESSOR DATA SHEET

### STANDARD FEATURES

- Select
- Simul-Select
- Mute
- PTT
- Volume Control
- Instant Recall Recorder
- Radio Emergency Signaling
- Cross-Patching
- Channel Change
- Scan
- ID Aliasing
- Private Calling
- Group Calling
- Radio-Check, Stun, Revive, Listen/Monitor, Status Messaging, Status Querying & Call Alerting



## **ACCESSORIES**

- Optional USB Headset
- Optional USB Desk Microphone
- Optional Desktop Speakers
- Optional USB Footswitch
- Custom VESA Mounting hardware included

# **SPECIFICATIONS**

Weight	3 lbs.
Dimensions	5.4" W x 4" D x 2" H
Operating Temperature Range	-20 to +60 °C
Analog Audio I/O	1 x Stereo TRS Output, 1 x Line Input
Power Requirements	12 VDC at 1.2 A maximum
Network I/O	2 x RJ45 PCIe GbE Ethernet Controllers
Graphics	Intel HD Graphics 400 (Braswell x86/MMX/SSE2)
Processor	Integrated Intel Celeron® CPU N3160 @ 1.60 GHz x 4
Memory	2 GB DDR3 RAM Standard
Storage	120 GB SSD
Video Outputs	1 x HDMI, 1 x VGA
Peripheral I/O	4 x USB 3.0
Operating System	Debian GNU/Linux 10 (Buster)

Specifications subject to change without notice. Check **css-mindshare.com** for downloads/updates.



